

ATTESTATION OF CONFORMITY

No. 25AE121374E004

The submitted sample of below equipment has been tested in according to Electromagnetic Compatibility Directive 2014/30/EU with the following standards. The test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the principal protection requirement of the EC Council Directive of 2014/30/EU.

Report No. : E04A25121374E00401
Applicant : VTAC EUROPE LTD
Address : Bulgaria, Plovdiv 4000, Bul.L.Karavelow 9B
Manufacturer : VTAC EUROPE LTD
Address : Bulgaria, Plovdiv 4000, Bul.L.Karavelow 9B
Description of Product : Portable Power Station
Model No. : VT-10008
Trade Mark : 
Rating : See the Attachment for details
Test Standards : EN 55032:2015/A1:2020
EN 55035:2017/A11:2020
EN IEC 61000-3-2:2019/A2:2024
EN 61000-3-3:2013/A2:2021

After preparation of the necessary technical documentation as well as the EU declaration of conformity, the CE marking can be affixed on the product if all relevant effective EU-directives or regulations related to CE marking have been complied with. The EU declaration of conformity is issued under the sole responsibility of the applicant or manufacturer.



Shawn Wen
Laboratory Manager
Date of Issue: January 08, 2026

This attestation of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the production of the products.

Guangdong Global Testing Technology Co., Ltd.

Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808
Web: www.gtgroup.com E-mail: info@gtgroup.com Tel.: 86-4007558988

No. 25AE121374E004

Attachment:

Model	Ratings
VT-10008	<p>Battery: 1229Wh, 51.2V $\overline{=}$</p> <p>Discharge temperature range: -20-45°C</p> <p>Charge temperature range: 0-45°C</p> <p>AC Input:220-240V~, 50/60Hz, 10A max, 1800W max</p> <p>Solar/Car input x1: 13-45V $\overline{=}$ 12A max., 400W max.</p> <p>AC socket x3 (Inverter Mode):220-240V~, 50/60Hz, 12A max., 1800W max.</p> <p>AC socket (Bypass Mode) x3:220-240V~, 50/60Hz, 10A max., 1800W max.</p> <p>Cigarette lighter output/DC 5521 total: 126W max.</p> <p>Cigarette lighter output: 12.6V $\overline{=}$ 10A max., 126W max.</p> <p>DC 5521 output x2: 12.6V $\overline{=}$ 3A, 40.8W max.</p> <p>USB-C1/C2 output: 5/9/12/15V $\overline{=}$ 3A, 20V $\overline{=}$ 5A, 100W max.</p> <p>USB-A1/A2 output: 5V $\overline{=}$ 3A, 9V $\overline{=}$ 2A, 12V $\overline{=}$ 1,5A, 18W max.</p> <p>USB-A3/A4 output: 5V $\overline{=}$ 2.4A, 12W max.</p>